



ETS-D5

/// Data Sheet

Electronic contact thermometer with 3 patented operating modes of IKA

- With optimised PID control
- RESET function
- Incl. stainless steel sensor H 62
- With 3 patented operating modes
- Ensures perfect temperature control in liquid mediums, without overshooting the set temperature, even in the case of quick heating



designed for scientists

Technical Data

Temperature measuring range [°C]	-50 - 450
Temperature measurement resolution [K]	0.1
Accuracy of temperature measurement [K]	±0.2 + tolerance PT1000 (DIN IEC 751 Class A)
Set temperature resolution [±K]	0.1
Heat control accuracy of medium with sensor [±K]	0.5
Immersion depth max. [mm]	200
Permissible ON time [%]	100
Dimensions (W x H x D) [mm]	82 x 83 x 22
Weight [kg]	0.2
Permissible ambient temperature [°C]	0 - 60
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 54
DC Voltage [V=]	8 - 16
Current consumption [mA]	15

000 «Диаэм»

Москва
ул. Магаданская, д. 7, к. 3 ■ тел./факс: (495) 745-0508 ■ sales@dia-m.ru

www.dia-m.ru

С.-Петербург
+7 (812) 372-6040
spb@dia-m.ru

Новосибирск
+7 (383) 328-0048
nsk@dia-m.ru

Воронеж
+7 (473) 232-4412
vrn@dia-m.ru

Йошкар-Ола
+7 (927) 880-3676
nba@dia-m.ru

Красноярск
+7 (923) 303-0152
krsk@dia-m.ru

Казань
+7 (843) 210-2080
kazan@dia-m.ru

Ростов-на-Дону
+7 (863) 303-5500
rnd@dia-m.ru

Екатеринбург
+7 (912) 658-7606
ekb@dia-m.ru

Кемерово
+7 (923) 158-6753
kemerovo@dia-m.ru

Армения
+7 (094) 01-0173
armenia@dia-m.ru

